

SAFETY DATA SHEET

1. Identification

Important information *** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any

unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action

being taken by HP. ***

HP Color LaserJet W2010A-X Black Print Cartridge **Product identifier**

Other means of identification

Recommended use This product is a black toner preparation that is used in HP Color LaserJet Enterprise M856dn,

M856x, HP Color LaserJet Managed E85055dn series printers.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

1501 Page Mill Road Palo Alto, CA 94304-1112

United States

Telephone 650-857-1501

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048

HP Inc. Customer Care

Line

1-800-474-6836 (Toll-free within the US) (Direct) 1-208-323-2551

hpcustomer.inquiries@hp.com Email:

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards** Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements

None. Hazard symbol None. Signal word

Hazard statement Not available.

Precautionary statement

Prevention Not available. Not available. Response Not available. Storage **Disposal** Not available.

Hazard(s) not otherwise

classified (HNOC) carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not

Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly

present this carcinogenic risk.

GHS Supplemental information This product is not classified as hazardous according to OSHA CFR 1910.1200 (HazCom 2012).

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Styrene acrylate copolymer		CBI	<85

Material name: W2010A-X SDS US

15053 Version #: 02 Revision date: 07-Dec-2019 Issue date: 25-Sep-2019

Chemical name	Common name and synonyms	CAS number	%
Black Pigment*		1333-86-4*	<10
Wax	Wax	CBI	<10
Amorphous silica	Amorphous silica	7631-86-9	<3

4. First-aid measures

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at Eye contact

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a Ingestion

physician.

Not available.

Most important

symptoms/effects, acute and

delayed

5. Fire-fighting measures

Suitable extinguishing media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

Like most organic material in powder form, toner can form explosive dust-air mixtures when finely

dispersed in air. Not available.

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

If fire occurs in the printer, treat as an electrical fire.

Specific methods None established.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Minimize dust generation and accumulation.

Methods and materials for containment and cleaning up Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust

explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with

federal, state, and local regulations.

Environmental precautions

Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.

7. Handling and storage

Precautions for safe handling

Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with

adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Conditions for safe storage, including any incompatibilities Keep out of the reach of children. Keep tightly closed and dry. Store at room temperature. Store away from strong oxidizers.

Value

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Type PEL Black Pigment (CAS 3.5 mg/m3 1333-86-4)

US. ACGIH Threshold Limit Values

Form Components Type Value Black Pigment (CAS TWA 3 mg/m3 Inhalable fraction. 1333-86-4)

Material name: W2010A-X SDS US **US. NIOSH: Pocket Guide to Chemical Hazards**

Value Components Type Amorphous silica (CAS **TWA** 6 mg/m3 7631-86-9) Black Pigment (CAS **TWA** 0.1 mg/m3 1333-86-4)

Biological limit values No biological exposure limits noted for the ingredient(s).

USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) **Exposure guidelines**

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

mg/m3

TRGS 900 (Luftgrenzwert) - 10 mg/m3 (Einatembare partikel), 3 mg/m3 (Alveolengängige fraktion)

Appropriate engineering

controls

Use in a well ventilated area.

Individual protection measures, such as personal protective equipment

Not available. Eye/face protection

Skin protection

Not available. Hand protection Other Not available. Not available. Respiratory protection Thermal hazards Not available.

9. Physical and chemical properties

Appearance Fine powder

> Solid. Physical state **Form** solid Color Black.

Odor Slight plastic odor **Odor threshold** Not available. Not applicable Ηq Melting point/freezing point Not available. Not applicable Initial boiling point and boiling

range

Flash point Not applicable **Evaporation rate** Not applicable Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not flammable

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not applicable Vapor density Not applicable

Solubility(ies)

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient

(n-octanol/water)

Not available.

Not applicable **Auto-ignition temperature** > 392 °F (> 200 °C) **Decomposition temperature**

Material name: W2010A-X SDS US

15053 Version #: 02 Revision date: 07-Dec-2019 Issue date: 25-Sep-2019

Viscosity Not applicable

Other information

Oxidizing properties No information available.

Percent volatile 0 % estimated

Softening point 176 - 266 °F (80 - 130 °C)

Specific gravity 1 - 1.2

10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable under normal storage conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Imaging Drum: Exposure to light

Incompatible materials Strong oxidizers

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin contactContact with skin may result in mild irritation.Eye contactContact with eyes may result in mild irritation.IngestionIngestion is not a likely route of exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Product Species Test Results

W2010A-X

<u>Acute</u>

LD50 > 2000 mg/kg
Components Species Test Results

Black Pigment (CAS 1333-86-4)

Acute Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritationBased on available data, the classification criteria are not met. **Serious eye damage/eye**Based on available data, the classification criteria are not met.

irritation

mation

Respiratory or skin sensitization

Respiratory sensitizationBased on available data, the classification criteria are not met. **Skin sensitization**Based on available data, the classification criteria are not met.

Germ cell mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Material name: W2010A-X SDS US

Black Pigment (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

12. Ecological information

Ecotoxicity LC50: > 100 mg/l, Fish, 96.00 Hours

Product		Species	Test Results
W2010A-X			
Aquatic			
Algae	ErC50	Algae	> 100 mg/l, 72 Hours
Crustacea	EC50	Crustacea	> 100 mg/l, 48 Hours
Fish	LC50	Fish	> 100 mg/l, 96 Hours
Persistence and degradability	Not available.		
Bioaccumulative potential	Not available.		
Mobility in soil	Not available.		
Other adverse effects	Not available.		

13. Disposal considerations

Disposal instructions

> Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

14. Transport information

Further information

Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

15. Regulatory information

US federal regulations

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories**

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Material name: W2010A-X SDS US

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (AIRBORNE, UNBOUND PARTICLES Listed: February 21, 2003 OF RESPIRABLE SIZE [<= 10 MICROMETERS]) (CAS

1333-86-4)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Black Pigment (CAS 1333-86-4)

Regulatory information

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

16. Other information, including date of preparation or last revision

Issue date25-Sep-2019Revision date07-Dec-2019

Version # 02

Other information This SDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

Material name: W2010A-X SDS US

15053 Version #: 02 Revision date: 07-Dec-2019 Issue date: 25-Sep-2019

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: W2010A-X SDS US